



SolarEdge Single Phase Inverters

SE2200 - SE6000



INVERTERS

Specifically designed to work with power optimizers

- Superior efficiency (97.6%)
- Small, lightweight and easy to install
- Built-in module-level monitoring
- Internet connection through Ethernet or Wireless
- IP65 – Outdoor and indoor installation
- Fixed voltage inverter, DC/AC conversion only
- Compatible with the StorEdge Interface for Smart Energy Management StorEdge™ applications



Single Phase Inverters

SE2200 - SE6000

	SE2200	SE3000	SE3500	SE4000	SE5000	SE6000	
OUTPUT							
Rated AC Power Output	2200	3000	3500	4000	5000 ⁽¹⁾	6000	VA
Maximum AC Power Output	2200	3000	3500	4000	5000 ⁽¹⁾	6000	VA
AC Output Voltage (Nominal)	220 / 230						Vac
AC Output Voltage Range	184 - 264.5						Vac
AC Frequency (Nominal)	50 / 60 ± 5						Hz
Maximum Continuous Output Current	12	16.5 ⁽²⁾	19.5 ⁽²⁾	22 ⁽²⁾	27	27	A
Residual Current Detector / Residual Current Step Detector	300 / 30						mA
Utility Monitoring, Islanding Protection, Country Configurable Thresholds	Yes						
INPUT							
Maximum DC Power (Module STC)	2950	4050	4700	5400	6750	8100	W
Transformer-less, Ungrounded	Yes						
Maximum Input Voltage	500						Vdc
Nominal DC Input Voltage	350						Vdc
Maximum Input Current	8.5	11.5	13.5	15.5	19.5	23	Adc
Reverse-Polarity Protection	Yes						
Ground-Fault Isolation Detection	600kΩ Sensitivity						
Maximum Inverter Efficiency	97.6						%
European Weighted Efficiency	97.6	97.6	97.5	97.5	97.4	97.4	%
Nighttime Power Consumption	< 2.5						W
ADDITIONAL FEATURES							
Supported Communication Interfaces ⁽³⁾	RS485, Ethernet, ZigBee (optional), Wi-Fi (optional), Built-in GSM (optional)						
Smart Energy Management	Export Limitation, StorEdge applications						
STANDARD COMPLIANCE							
Safety	IEC-62103 (EN50178), IEC-62109						
Grid Connection Standards	VDE 0126-1-1, VDE-AR-N-4105, AS-4777, RD-1663, DK 5940						
Emissions	IEC61000-6-2, IEC61000-6-3, IEC61000-3-11, IEC61000-3-12, FCC part15 class B						
RoHS	Yes						
INSTALLATION SPECIFICATIONS							
AC Output	Cable Gland - diameter 9-16						mm
DC Input	1 MC4 pair			2 MC4 pairs			
Dimensions (HxWxD)	540 x 315 x 172			540 x 315 x 191			mm
Weight	20.2			21.7			kg
Cooling	Natural Convection						
Noise	<25						dBA
Operating Temperature Range	-20 - +50 (M40 version -40 - +50)						°C
Protection Rating	IP65 - Outdoor and Indoor						
Bracket Mounted (Bracket Provided)							

⁽¹⁾ Limited to 4600VA when inverter is set to South Africa

⁽²⁾ For inverters with an AC current limit of 16A please refer to the "SE3000-4000-16A Inverter" datasheet

⁽³⁾ Refer to Datasheets -> Communications category in Downloads page for specifications of optional communication options: <http://www.solaredge.com/groups/support/downloads>

